

Issue Date: 1-1-94  
Supersedes: 3-1-93  
Prepared by Harry Austin

P.C.I. INDUSTRIES, INC.  
P.O. BOX 9845  
1661 OLD DIXIE HIGHWAY  
RIVIERA BEACH, FL 33419  
407-844-0241 EMERGENCY & Info.  
(Business Hours)

\*24-HOUR CONTACT

1-800-424-9300

[ONLY for EMERGENCIES  
involving a spill, leak  
fire, explosion or  
accident involving this  
product.]

This MSDS complies with OSHA 29 CFR 1910.1200 (The Hazard Communication Standard)

\*\*\*\*\*

----- SECTION I - PRODUCT IDENTIFICATION -----

PRODUCT IDENTITY (Trade Name) : **EZ WELD FIFTY-FOUR-FIFTY PIPE THREAD COMPOUND**  
DOT HAZARD CLASSIFICATION : Flammable liquid, 3.1

----- SECTION II - HAZARDOUS INGREDIENTS -----

<u>SPECIFIC CHEMICAL NAME</u>	<u>CAS#</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>STEL</u>	<u>%WT</u>
-------------------------------	-------------	-----------------	------------------	-------------	------------

None

Carcinogenicity - None of the above hazardous ingredients are considered to be carcinogenic by NTP, IARC, or OSHA, thus there is no reason to assume the mixture would be carcinogenic as no new compounds are being formed thru chemical reaction.

HMIS / NFPA HAZARD CODE      Health - 1                      Flammability - 1                      Reactivity - 0

----- SECTION IIA- NON-HAZARDOUS INGREDIENTS -----

All

----- SECTION 313 - SUPPLIER NOTIFICATION -----

This product contains toxic chemicals (\* See Above) subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-to-Know Act of 1986 and of 40CFR37

----- SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS -----

Boiling Point - 500°F	Specific Gravity (H <sub>2</sub> O=1) - > 1
Auto Ignition - Unknown	Vapor Pressure - Less than 1 mm Hg @ 63°F
Percent Volatiles - 30%	Vapor Density (Air=1) - > 1
Solubility in Water - 0.1%	Evaporation Rate (N-Butyl Acetate=1) - 0.02

Appearance and Odor - White paste with very slight oil odor.

----- SECTION IV - FIRE & EXPLOSION HAZARD DATA -----

Flash Point (TCC) - 190°F  
Flammable Limits in Air - Lower - 1%      Upper - 6%  
Extinguishing Media - Alcohol resistant foam, carbon dioxide or dry chemicals.  
Firefighting Procedures: Wear self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode when fighting fires.  
Special Fire & Explosion Hazards: Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heater, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point.

Hazardous Decomposition Products : May form toxic materials: carbon dioxide, carbon monoxide and various hydrocarbons.



## MATERIAL SAFETY DATA SHEET

P.C.I. INDUSTRIES, INC.  
 P.O. BOX 9845  
 1661 OLD DIXIE HIGHWAY  
 RIVIERA BEACH, FLORIDA 33404

407-844-0241 EMERGENCY &amp; INFORMATION

PAGE 3 of 3

\*\*\*\*\*  
 -----SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE-----

Accidental Release or Spill : Extinguish and do not turn on any ignition source until area is determined to be free from explosion or fire hazards.

Small Spill: Absorb with earth, sand or similar inert material and dispose of with solid waste according to federal, state and local regulations. Flush spill area with water.

Large Spill: Erect temporary (or permanent) dike to contain spill. Collect and destroy by liquid incineration. Otherwise, dilute with water and using inert absorbent material shovel into containers to be disposed of as solid waste according to federal, state and local regulations.

Waste Disposal: Comply with federal, state and local regulations. If permits and regulations allow, may be incinerated, allowed to evaporate or solidified with inert material and disposed of.

Precautions to be taken in Handling and Storage:

Keep away from heat, sparks, and flame. Avoid breathing vapor. Avoid contact with eyes, skin, and clothing. Keep container closed. Use with adequate ventilation. Wash thoroughly after using.

Other Precautions: Containers of this material may be hazardous when emptied since emptied containers retain product residues (vapor, liquid, and/or solid). All hazard precautions given in data sheet above must be observed.

-----SECTION VIII - CONTROL MEASURES-----

Respiratory Protection: If the TLV of the product or any component of it is exceeded, a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSA/MSHA respirators under specified conditions.

Ventilation: If the product is used in a confined area, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV (s). Explosion proof equipment is advised.

Protective Gloves: Rubber, butyl or other impervious gloves.

Eye Protection: Chemical safety splash glasses.

Other Protective Clothing or Equipment: Eye bath, safety shower, face shield, rubber safety boots.

-----  
 The information accumulated herein is believed to be accurate but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.