



213 PURPLE PRIMER/ CLEANER

LOW
VOC

GENERAL DESCRIPTION:

E-Z Weld 213 Primer Cleaner is a product that both cleans dirt, oils and greases from pipe and fitting surfaces as well as softens and swells the joints prior to cementing. The use of 213 provides for stronger joints. It is highly recommended for the installation of pipe and fittings over 3" diameter.

APPLICATION:

E-Z Weld Primer/Cleaner may be used on all PVC and CPVC pipes and fittings, all sizes and all schedules. Apply liberal coat to the outer surface of the pipe end and the inner surface of the fitting socket using a dauber supplied with the can or other suitable applicator. Do not puddle primer into the socket. Unlike pipe cleaner do not wipe off primer. Apply cement according to the instructions on the label of cement while primer is still wet.



Always follow instructions on the label.

Application temperature: -10°F to 110°F

Storage temperature: -10°F to 100 °F

CAUTION:

NSF and IAMPO (UPC) do not have a standard to certify a Primer/Cleaner. If local code requires the use of Primer this product or any other Primer/Cleaner should not be used.

PURPLE PRIMER WILL STAIN MOST MATERIAL AND CAN NOT BE REMOVED. HANDLE WITH CARE

QUALITY ASSURANCE:

Every batch of cement is carefully checked and monitored to assure consistently high quality standards. Records of every batch are kept. A sample of every batch is taken and kept at least one year. All ingredients are purchased from approved suppliers.

PHYSICAL PROPERTIES:

Color: Light Purple Shelf life: Unlimited (Unopened can)

Specific Gravity: 6.570

LOW VOC (VOLITILE ORGANIC COMPOUND)

Maximum VOC per SCAQMD 1168/316A: 550 g/l



213 PURPLE PRIMER/ CLEANER



AVAILABILITY:

Size	Part No. Regular	(UPC No.)	
1/4pt	21301	892996002560	<i>1/4 pt., 1/2 pt., Pt. And Qt. cans are supplied with dauber inside cap. Gallon sizes supplied with plain cap only.</i>
1/2pt	21302	892996002577	
Pt	21303	892996002584	
Qt	21304	892996002591	
Gal	21305	892996002607	

PACKAGING:

Size	1/4 Pt	1/2 Pt	Pt	Qt	Gal
Fluid oz	4	8	16	32	128
Liters	0.12	0.24	0.49	0.95	3.79
Units per case	24	24	12	12	6
Weight per case - Lb.	8	15	14	27	49
Weight per case - Kg	3.63	6.81	6.36	12.26	22.70
Cubic feet per case	0.28	0.42	0.43	0.73	1.12
Cubic meter per case	0.008	0.012	0.012	0.021	0.032
Cases per pallet	240	140	144	100	45

SAFETY PRECAUTIONS:

Ensure adequate ventilation to avoid vapor build up which may cause flash fire. Vapor build up may also cause dizziness, headaches or eye watering. If symptoms are experienced use respiratory protection (NOISH/MSHA TC 23 c or equivalent) or leave area and provide more fresh air. Avoid contact with eyes, skin and clothing by use of safety glasses and gloves. Professionals should consult ASTM Standard F 402-93 Safe Handling of Solvent Cements, Primers and Cleaners Used for Joining Thermoplastic Pipe and Fittings. Professional users should also read the Material Safety Data Sheet for the product.

Inhalation: If breathing is difficult vacate to fresh air. If breathing problems persist seek immediate medical attention.

Eyes: Flush eyes thoroughly with water for 15 minutes. Get immediate medical attention.

Internal: If swallowed give 1 or 2 glasses of water immediately, call physician, hospital or poison control immediately. **DO NOT INDUCE VOMITING.**

SHIPPING / TRANSPORTATION:

Material packaged in less than a liter size is exempted under "Limited Quantity Rules" by DOT. These packages may be shipped with the description ORM - D Consumer Commodity. Packages shipped under this description are not subject to shipping paper requirements for flammable materials.

For a liter and larger sizes (gallon and above container):

Proper shipping name: Compound Cleaning Liquid Flammable Class: 3 UN No: NA 1993 Packing group: PG II